


4 LOAD CELL STAINLESS STEEL SCALE



release date 15-11-2012



Measurement with application of 4 load cells is a guarantee of precise readout, regardless of load position on the weighing platform.

This platform scales series WPT/4H with 4 load cells are manufactured in fully stainless steel technology with stainless steel indicator series PUE C/31H with backlit LCD display. The indicator is installed on a 3 meter long cable with possibility of mounting on wall. WPT/4H is available with capacity from 300 kg/100g to 6000 kg/2000g.

Scales are powered from mains, RS 232 output is offered as standard.



Counting pieces



Checkweighing



Summing function

Technical data:

	WPT/4 300 H6	WPT/4 600 H6	WPT/4 300 H7	WPT/4 600 H7	WPT/4 1500 H7	WPT/4 1500 H8	WPT/4 3000 H8
Max capacity	300 kg	600 kg	300 kg	600 kg	1500 kg	1500 kg	3000 kg
Readability	100 g	200 g	100 g	200 g	500 g	500 g	1000 g
Tare range	-300 kg	-600 kg	-300 kg	-600 kg	-1500 kg	-1500 kg	-3000 kg
Pan size	800×800 mm	800×800 mm	1000×1000 mm	1000×1000 mm	1000×1000 mm	1200×1200 mm	1200×1200 mm
Working temperature	-10° - +40 °C						
Output signal	RS 232						
IP rating	IP 68 construction, IP 66/67 indicator						
Power supply	230V / 11V AC or 120V / 11V AC and internal accumulator						
Operation time on accumulators	~ 45 h (average)						
Display	LCD (backlit)						
Scale weight with indicator	59 kg	59 kg	84 kg	84 kg	94 kg	125 kg	130 kg
Platform height	88 mm	88 mm	88 mm	88 mm	88 mm	88 mm	111 mm

Technical data:

	WPT/4 1500 H8/9	WPT/4 3000 H8/9	WPT/4 1500 H9	WPT/4 3000 H9	WPT/4 3000 H10	WPT/4 6000 H10
Max capacity	1500 kg	3000 kg	1500 kg	3000 kg	3000 kg	6000 kg
Readability	500 g	1000 g	500 g	1000 g	1000 g	2000 g
Tare range	-1500 kg	-3000 kg	-1500 kg	-3000 kg	-3000 kg	-6000 kg
Pan size	1200×1500 mm	1200×1500 mm	1500×1500 mm	1500×1500 mm	1500×2000 mm	1500×2000 mm
Working temperature	-10° - +40 °C					
Output signal	RS 232					
IP rating	IP 68 construction, IP 66/67 indicator					
Power supply	230V / 11V AC or 120V / 11V AC and internal accumulator					
Time on accumulators	~45 h (average)					
Display	LCD (backlit)					
Scale weight with indicator	158 kg	165 kg	190 kg	200 kg	285 kg	350 kg
Platform height	88 mm	111 mm	88 mm	111 mm	111 mm	166 mm

Technical data:


	WPT/4 300/600 H6	WPT/4 300/600 H7	WPT/4 600/1500 H7	WPT/4 600/1500 H8	WPT/4 1500/3000 H8
Max capacity	300/600 kg	300/600 kg	600/1500 kg	600/1500 kg	1500/3000 kg
Readability	100/200 g	100/200 g	200/500 g	200/500 g	500/1000 g
Tare range	-600 kg	-600 kg	-1500 kg	-1500 kg	-3000 kg
Pan size	800x800 mm	1000x1000 mm	1000x1000 mm	1200x1200 mm	1200x1200 mm
Working temperature	-10° - +40 °C				
Output signal	RS 232				
IP rating	IP 68 construction, IP 66/67 indicator				
Power supply	230V / 11V AC or 120V / 11V AC and internal accumulator				
Operation time on accumulators	~45 h (average)				
Display	LCD (backlit)				
Scale weight with indicator	59 kg	84 kg	94 kg	125 kg	130 kg
Platform height	88 mm	88 mm	88 mm	88 mm	111 mm

Technical data:

	WPT/4 600/1500 H8/9	WPT/4 1500/3000 H8/9	WPT/4 600/1500 H9	WPT/4 1500/3000 H9	WPT/4 1500/3000 H10	WPT/4 3000/6000 H10
Max capacity	600/1500 kg	1500/3000 kg	600/1500 kg	1500/3000 kg	1500/3000 kg	3000/6000 kg
Readability	200/500 g	500/1000 g	200/500 g	500/1000 g	500/1000 g	1000/2000 g
Tare range	-1500 kg	-3000 kg	-1500 kg	-3000 kg	-3000 kg	-6000 kg
Pan size	1200x1500 mm	1200x1500 mm	1500x1500 mm	1500x1500 mm	1500x2000 mm	1500x2000 mm
Working temperature	-10° - +40 °C					
Output signal	RS 232					
IP rating	IP 68 construction, IP 66/67 indicator					
Power supply	230V / 11V AC or 120V / 11V AC and internal accumulator					
Operation time on accumulators	~45 h (average)					
Display	LCD (backlit)					
Scale weight with indicator	158 kg	165 kg	190 kg	200 kg	285 kg	350 kg
Platform height	88 mm	111 mm	88 mm	111 mm	111 mm	166 mm

Additional equipment:

Kafka thermal printer	PW-WIN 2004 computer software
Epson impactprinter	RAD-KEY 2000 computer software
Anti-dust case for Epson printer	REC-FS 2000 computer software
Stand for measuring indicator	RS 232 cable: scale - thermal printer: P0136
KR-04 converter Rs232 / Ethernet	RS 232 cable: scale - "Epson" printer: P0151
Large LCD WWG-2 (digit height 4,5")	RS 232 cable: scale - computer: P0108
LCD display in plastic casing	Cable for plugging to car lighter 12V: K0047
	LCD display in stainless steel casing



	max	A x B	C	D x E	S
WPT/4 300 H6	300kg	800x800mm	88±2mm	660x660mm	Ø80
WPT/4 600 H6	600kg	800x800mm	88±2mm	660x660mm	Ø80
WPT/4 300 H7	300kg	1000x1000mm	88±2mm	860x860mm	Ø80
WPT/4 600 H7	600kg	1000x1000mm	88±2mm	860x860mm	Ø80
WPT/4 1500 H7	1500kg	1000x1000mm	88±2mm	860x860mm	Ø80
WPT/4 1500 H8	1500kg	1200x1200mm	88±2mm	1060x1060mm	Ø80
WPT/4 3000 H8	3000kg	1200x1200mm	111mm	1060x1060mm	Ø80
WPT/4 1500 H8/9	1500kg	1200x1500mm	88±2mm	1060x1360mm	Ø80
WPT/4 3000 H8/9	3000kg	1200x1500mm	111mm	1060x1360mm	Ø80
WPT/4 1500 H9	1500kg	1500x1500mm	88±2mm	1360x1360mm	Ø80
WPT/4 3000 H9	3000kg	1500x1500mm	111mm	1360x1360mm	Ø80
WPT/4 3000 H10	3000kg	1500x2000mm	111mm	1360x1860mm	Ø80
WPT/4 6000 H10	6000kg	1500x2000mm	166mm	1360x1860mm	Ø100